


Expedite Scanning with a Small yet Functional Scanner



Scanning Speed
30 ppm / 60 ipm

* A4/Letter, Portrait, 300 dpi, Binary/Colour



- Space Saving
- Versatile Scanning
- Simple to Operate
- Less Scanning Delays




Space Saving with Compact Design

The compact body of KV-S1037 can fit in small and narrow spaces but it is packed with essential features to finish scanning jobs fast and efficient.



* Clearance required to set the feed tray and exit tray



Versatile Scanning with Various Scanning Options

Scanning various documents is made easy with KV-S1037. No more problem when scanning a long paper, passport, bankbook, or even embossed cards at once.



* Use the carrier sheet [KV-SS077] to scan passport and the mixed batch card guide to scan embossed cards.

Simple to Operate with 3 Single Touch and Touch Free Scanning

3 Single Touch Scanning

Simply press one of the buttons to scan and send the data to preset destinations.



* Jobs should be registered to the PC in advance.

Touch Free Scanning


Convenient for manual paper scanning. Just insert document directly into ADF to start scanning.



Less Scanning Delays with Reliable Roller System

Double Feed Prevention Roller System

The reverse separating rollers move the second and following pages backward to reduce the occurrence of double feeding. This allows fast and smooth scanning operations.



Specifications

Scanning Face	Duplex
Scanning Method	1 line colour CIS (300 dpi/600 dpi), Background: Black
Scanning Resolution*1	100 dpi - 600 dpi (1 dpi step) and 1,200 dpi (interpolated) Optical: 300/600 dpi (Automatic switch)
Scanning Speed*2 A4/Letter Binary/Colour (200 dpi, 300 dpi)	Simplex: 30 ppm, Duplex: 60 ipm
Double-Feed Detection	Ultrasonic (The length of documents that can be detected is 70 mm (2.8 in.) or more.)
Image Compression	MH, MMR, JPEG, JPEG2000
Binary Mode Halftone	Dither, Error Diffusion
ADF Document Size	Manual feeding: 48 mm x 54 mm - 216 mm x unlimited (1.9 in. x 2.1 in. - 8.5 in. x unlimited)*3 Automatic feeding: 48 mm x 54 mm - 216 mm x 356 mm (1.9 in. x 2.1 in. - 8.5 in. x 14 in.)
Thickness	Paper: 0.04 mm - 0.5 mm (1.6 mils - 19.7 mils) Passport*4: 3.0 mm (118.1 mils) (including carrier sheet) ISO format card: 0.76 mm (0.03 in.) Embossed card up to 1.24 mm (0.049 in.) Note: 1 mil = 0.001 in.
Weight	20 g/m ² - 413 g/m ² (5 lb. - 110 lb.)
Feed Tray Capacity	50 sheets (80 g/m ² [21 lb.] High-quality woodfree paper)*5
Supported Operating System	Windows Vista® SP2 (32 bit/64 bit) Windows® 7 (32 bit/64 bit), Windows 8 (32 bit/64 bit) Windows 8.1 (32 bit/64 bit), Windows 10 (32 bit/64 bit) Windows Server® 2003 SP2 (32 bit/64 bit) Windows Server® 2003 R2 SP2 (32 bit/64 bit) Windows Server® 2008 SP2 (32 bit/64 bit) Windows Server® 2008 R2 SP1 (64 bit) Windows Server® 2012 (64 bit), Windows Server® 2016 (64 bit) Mac OS X 10.8 - 10.11, macOS 10.12 - 10.14, Red Hat® Enterprise Linux® Desktop 6/7, Ubuntu® 12/14/15/16/17/18/19

*1 When scanning a document larger than A5 size at resolutions over 600 dpi, the scanning may fail due to insufficient memory.

*2 The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring method of Panasonic.

*3 Using "Long Paper", you can scan long documents by splitting them into smaller parts.

*4 Use the carrier sheet (KV-SS077) to scan passport. Depending on the condition (operating environment, dirt, scratches, etc.) of the carrier sheet or passport, the image processing function may not work properly. Scan beforehand to confirm the scanned image.

*5 Depending on the paper type or operating environment (temperature, humidity, etc.), the unit may not feed the documents properly.
When paper weight is more than 209 g/m² (55 lb.): 5 sheets (A4, High-quality woodfree paper).
When installed the mixed batch card guide: 20 sheets (80 g/m² [21 lb.], High-quality woodfree paper).

*6 The power requirement differs depending on the country/area.

Interface	USB 3.1 Gen1 (backward compatible)
External Dimensions (W X D X H)	303 mm x 177 mm x 137 mm (12.0 in. x 7.0 in. x 5.4 in.)
Weight	2.7 kg (5.9 lb.)
Power Requirement*6	AC 100 - 240 V, 50/60 Hz
Power Consumption	Maximum (Scanning) 25 W or less (DC 16 V 1.5 A) Minimum (Ready) 6 W or less Sleep 1.6 W or less Power Off 0.3 W or less
Operating Environment	Temperature: 5 °C - 35 °C (41 °F - 95 °F) Humidity: 20 % - 80 % RH
Storage Environment	Temperature: -10 °C - 50 °C (14 °F - 122 °F) Humidity: 8 % - 75 % RH
Accessories	CD-ROM: Device driver, ISIS driver software, TWAIN driver software, WIA driver software, User utility, Scan Button Setting Tool, Image Capture Plus, Operating Manual, Control sheet Quick Installation Guide, Power cord, AC adaptor, 1.5 m USB cable (USB 3.1), Mixed batch card guide, Shading paper, Guidance sticker, Correction sticker
Options	Options Flatbed Scanner: KV-SS081, Roller exchange kit: KV-SS058, Roller cleaning paper: KV-SS03, Carrier sheet: KV-SS077

Trademarks and registered trademarks

- ISIS is a registered trademark or trademark of Open Text Corporation.
- Windows, Windows Vista and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- Mac, OS X and macOS are trademarks of Apple Inc., registered in the U.S. and other countries.
- Linux is a registered trademark or a trademark of Linus Torvalds in the United States and other countries.
- Red Hat and Red Hat Enterprise Linux are registered trademarks or trademarks of Red Hat, Inc. in the United States and other countries.
- Ubuntu is a registered trademark or a trademark of Canonical Ltd. in the United States and other countries.
- All other brand or product names are the property of their respective holders.

This product is designed to reduce hazardous chemical substances in accordance with the RoHS directive.

- All photographs in this brochure are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.



DISTRIBUTED BY:

Panasonic

Document Scanner: <https://panasonic.net/cns/office/products/scanner/>

Printed in Japan MG-SCNL034EN 1910NSP/ZZZ-U4