
C-Series MICROFILM APERTURE CARD SCAN SYSTEMS

THE LATEST DIGITAL
IMAGING TECHNOLOGY
IN A COMPACT DESKTOP
DESIGN



Create digital images from microfilm aperture cards that can be instantly accessed, searched, viewed, printed or emailed. Simple operation makes the C-Series an ideal digital alternative to reader-printers.







The easier, simpler, better way to scan

Key Features and Technical Specifications C-Series Aperture Card Scanners

The C-Series includes two models: the desktop **C Drive-X** for on-demand scanning of single aperture cards and the **C400** with Hollerith read and auto-feed hopper for unattended batch scanning.

- · Affordable and convenient solution for the conversion of your microfilm aperture cards to digital images
- · Latest digital imaging technology: create high-quality images at full resolution; go straight from microfilm to digital image file
- Hollerith (punch) data is automatically read and used to select drawing sizes and file names if required (C400 only)
- Dual-save allows both bitonal and grayscale images to be saved from a single scan of the card
- · Auto white balance (AWB) produces the best possible grayscale and bitonal images from each card
- Fully compatible with Windows 7 32-bit and 64-bit operating systems and Windows 8 Professional
- High-speed USB plug and play connectivity; reduces set-up time
- Simple and effective interface
- Virtual rescan: automatically reprocesses the scanned image with alternative imaging parameters. No need to physically rescan the aperture card.
- Designed for microfilm: optics, scan engine and Smartcode image processing algorithms all developed by Wicks and Wilson engineers specifically for microfilm scanning
- · Flexible scanning solution: both models are capable of scanning any ISO aperture card with no extras or modifications to purchase

Model	C Drive X	C400
Resolution	100-400dpi	100-400dpi
Speed (A2/C Size, 200dpi)*	<10s	370
Speed (A2/C Size 400dpi)*	<13s	300
Hopper-feed	Single card manual	150 card automated batch feed
Hollerith entry	Manual	Automatic (IBM, MIL STD 804B)
Reduction ratio	7.5x to 40x (variable)	
Dual-save (grayscale and bitonal)	Yes	
Scaling accuracy	+/0.5%	
File formats (bitonal)	TIFF, CALS, PNG and PDF	
File formats (grayscale)	JPEG, BMP, RAW TIFF, PNG, and PDF	
Agency approvals	CE, UL, cUL	
RoHS compliance	YES	
Size (W \times D \times H)	$150 \text{mm} \times 200 \text{mm} \times 90 \text{mm} (59" \times 79" \times 35")$	170mm x 460mm x 210mm (67" x 181" x 83")
Weight	1.9kg (4.2lbs)	5.8kg (12.8lbs)
Power requirement	110/240V; 250/170mA external power pack	
Controller PC	See website (www.wwl.co.uk) for current specifications	
Operating system	Windows 7 Professional (32 or 64 bit) and Windows 8 Professional	

^{*} Maximum speed dependent on PC configuration

Rev 11/14

Wicks and Wilson, 6 Rutherford Road, Daneshill Industrial Estate, Basingstoke, Hampshire, RG24 8PD, UK



Europe Telephone +44 (0) 1256 842211 Fax +44 (0) 1256 840997

North America Telephone 240.215.0224 Fax 240.215.0234

Email wwl@thecrowleycompany.com Web www.wwl.co.uk